

Share:



RBC2



Description: Genuine APC RBC(TM) are tested and certified for compatibility to restore UPS performance to the original specifications.

Includes : All required connectors , Battery recycling guide , Installation Guide , Reusable packaging

- User Manual
- Product Registration
- Product FAQs

Product Overview

Technical Specifications

Documentation

Input

[Print Technical Specification](#)

Number of Power Cords 1

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting	--
Expected Battery Life (years)	3 - 5
RBC Quantity	1

Physical

Maximum Height	94mm , 9.4CM
Maximum Width	64mm , 6.4CM
Maximum Depth	151mm , 15.1CM
Net Weight	2.5KG
Shipping weight	2.77KG
Shipping Height	89mm , 8.9CM
Shipping Width	175mm , 17.5CM
Shipping Depth	213mm , 21.3CM
Color	Black
Units per Pallet	240.0

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters

Conformance

Standard warranty 1 year repair or replace

Sustainable Offer Status

RoHS Compliant

REACH REACH: Contains No SVHCs

PEP Available in Documentation tab

EOLI Available in Documentation tab

Proposition 65 Warning Available in Documentation tab