

Share:



RBC48



Description: Genuine APC RBC(TM) are tested and certified for compatibility to restore UPS performance to the original specifications.

Includes : All required connectors , Battery recycling guide , Installation Guide , Reusable packaging

- User Manual
- Product Registration
- Product FAQs

Product Overview

Technical Specifications

Documentation

Batteries & Runtime

[Print Technical Specification](#)

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting	Stand alone battery stack
Battery manufacturer	--
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery blocks per string	2

Physical

Maximum Height	108mm , 10.8CM
Maximum Width	132mm , 13.2CM
Maximum Depth	150mm , 15.0CM
Net Weight	5.0KG
Shipping weight	5.91KG
Shipping Height	168mm , 16.8CM
Shipping Width	168mm , 16.8CM
Shipping Depth	224mm , 22.4CM
Units per Pallet	75.0

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters

Conformance

Standard warranty

1 year repair or replace

Sustainable Offer Status

RoHS

Compliant

REACH

REACH: Contains No SVHCs

PEP

Available in Documentation tab

EOLI

Available in Documentation tab

Proposition 65 Warning

Available in Documentation tab