



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	User manual
--------------------	-------------

Physical

Cable length	1.22 M
Colour	Black
Depth	39 Cm
Height	19 Cm
Net weight	7.5 Kg
Width	14 Cm

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Plug standard	IEC 60320 C14
Input voltage limits	140...300 V 230 V AC
Input voltage	230 V AC 1 phase

Output

Rated power in W	650 W
Maximum configurable power in W	650 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	6 IEC 320 C13
Output voltage	230 V AC 1 phase

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Conformance

Product certifications	CE CB
Standards	CE EN/IEC 62040-1 EN/IEC 62040-2
Equipment protection policy	Lifetime : 50000 euros

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage altitude	0...3000 M
Acoustic level	40 dBA
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 H
Liquid value	0
Battery voltage	12 V

Communications & Management

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous-tone alarm

Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

Packing Units

Package 1 Weight	8.5 Kg
Package 1 Height	29.7 Cm
Package 1 width	23.5 Cm
Package 1 Length	49.5 Cm
SCC14	10731304404504

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : **Commercialised**