

Share:



SRT192RMBP2



Description: Extended-run battery systems provide flexible runtime to critical Smart-UPS applications.
Includes : Installation guide , Warranty card



- User Manual
- Replacement Battery
- Product Registration
- Product FAQs

Product Overview

Technical Specifications

Documentation

Drawings

Options

Output

[Print Technical Specification](#)

Battery Output Voltage +/- 192V

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting	Stand alone battery stack
Expected Battery Life (years)	3 - 5
RBC Quantity	2

Physical

Maximum Height	130mm , 13.0CM
Maximum Width	432mm , 43.2CM
Maximum Depth	682mm , 68.27CM
Rack Height	3U
Net Weight	91.0KG
Shipping weight	105.5KG
Shipping Height	420mm , 42.0CM
Shipping Width	600mm , 60.0CM
Shipping Depth	1000mm , 100.0CM
Color	Black
Units per Pallet	1.0

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (no %
Operating Elevation	0-3000meters

Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (no %
Storage Elevation	0-15000meters
Conformance	
Approvals	OSHPD
Standard warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
Proposition 65 Warning	Available in Documentation tab