

Share:



# SURT192RMLBP2



Description: Extended-run battery systems provide flexible runtime to critical Smart-UPS applications.  
Includes : All required connectors , Rack Mounting brackets , User Manual

- User Manual
- Replacement Battery
- Product Registration
- Product FAQs

[Product Overview](#)

**[Technical Specifications](#)**

[Documentation](#)

[Options](#)

## Batteries & Runtime

[Print Technical Specification](#)

Battery type	VRLA
Battery mounting	19 inch Battery tray
Expected Battery Life (years)	3 - 5
RBC Quantity	4

## Physical

Maximum Height	263mm , 26.3CM
Maximum Width	432mm , 43.2CM
Maximum Depth	739mm , 73.9CM
Rack Height	6U
Net Weight	181.82KG
Shipping weight	220.45KG
Shipping Height	432mm , 43.2CM
Shipping Width	610mm , 61.0CM
Shipping Depth	1003mm , 100.3CM
Color	Black
Units per Pallet	1.0

## Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (no %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (no %
Storage Elevation	0-15000meters

## Conformance

---

Approvals OSHPD

---

Standard warranty 2 years repair or replace

---

## Sustainable Offer Status

---

RoHS Compliant

---

PEP Available in Documentation tab

---

EOLI Available in Documentation tab

---