

Share:



## XBP48RM1U-LI



Description: Extended-run battery systems provide flexible runtime to critical Smart-UPS applications.  
Includes : 4 post rail kit , Comms cable , Grounding Cable , Installation guide , Rack Mounting brackets



- User Manual
- Product Registration
- Product FAQs

Product Overview

Technical Specifications

Documentation

### Output

[Print Technical Specification](#)

Battery Output Voltage 48

### Batteries & Runtime

Battery type	Lithium Ion
Battery mounting	Rack Mount
Expected Battery Life (years)	5 - 10
Battery Design Life	--

### Physical

Maximum Height	43mm , 4.3CM
Maximum Width	432mm , 43.2CM
Maximum Depth	521mm , 52.1CM
Rack Height	1U
Net Weight	12.0KG
Shipping weight	16.4KG
Shipping Height	200mm , 20.0CM
Shipping Width	600mm , 60.0CM
Shipping Depth	850mm , 85.0CM
Color	Black with silver front bezel
Units per Pallet	8.0

### Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (no %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C

Storage Relative Humidity	0 - 95 (no %
---------------------------	--------------

Storage Elevation	0-15000meters
-------------------	---------------

**Conformance**

---

Approvals	UL 1973
-----------	---------

Standard warranty	5 year repair or replace
-------------------	--------------------------

**Sustainable Offer Status**

---

RoHS	Compliant
------	-----------

REACH	REACH: Contains No SVHCs
-------	--------------------------

Battery Directive	Compliant
-------------------	-----------